

SEOHAN ANTAMINE CO. LTD TEST REPORT

SCOPE OF WORK

ICC-ES AC92 SECTION 4.7.1.1 TESTING ON HPL, WALL CLADDING

REPORT NUMBER

L3571.04-109-44

TEST DATE(S)

12/02/20 - 12/03/20

ISSUE DATE

01/14/21

REVISED DATE

01/15/21

RECORD RETENTION END DATE

12/03/24

PAGES


15

DOCUMENT CONTROL NUMBER

ATI 00479 (07/24/17)

RT-R-AMER-Test-2805

© 2017 INTERTEK





Total Quality. Assured.

130 Derry Court
York, Pennsylvania 17406

Telephone: 717-764-7700
Facsimile: 717-764-4129
www.intertek.com/building

TEST REPORT FOR SEOHAN ANTAMINE CO. LTD

Report No.: L3571.04-109-44

Revision: 1

Date: 01/15/21

REPORT ISSUED TO

SEOHAN ANTAMINE CO. LTD

165B-6L Namdong Industrial Complex
Incheon, Namdong-Gu 21688
SOUTH KOREA

SECTION 1

SCOPE

Intertek Building & Construction (B&C) was contracted by Seohan Antamine Co. Ltd to perform testing in accordance with ICC-ES AC92 Section 4.7.1.1 on their HPL, wall cladding. Results obtained are tested values and were secured by using the designated test method(s). Testing was conducted at Intertek B&C test facility in York, Pennsylvania.

This report does not constitute certification of this product nor an opinion or endorsement by this laboratory.

For INTERTEK B&C:

COMPLETED BY:	Richard E. Hartman III
TITLE:	Technician – Product Testing
SIGNATURE:	
DATE:	01/15/21

REVIEWED BY:	Timothy J. McGill
TITLE:	Manager – Product Testing
SIGNATURE:	
DATE:	01/15/21

REH:nls

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample(s) tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

TEST REPORT FOR SEOHAN ANTAMINE CO. LTD

Report No.: L3571.04-109-44

Revision: 1

Date: 01/15/21

SECTION 2**TEST METHOD(S)**

The specimens were evaluated in accordance with the following:

AC92, *Acceptance Criteria For Polymer-Based, Polymer-Modified and High-Pressure Laminate Exterior and Interior Wall Cladding*

ASTM E330/E330M-14 (Procedure B), *Standard Test Method for Structural Performance of Exterior Windows, Doors, Skylights and Curtain Walls by Uniform Static Air Pressure Difference*

SECTION 3**MATERIAL SOURCE**

Test specimen(s) were provided by the client. Representative samples of the test specimen(s) will be retained by Intertek B&C for a minimum of four years from the test completion date.

SECTION 4**EQUIPMENT**

Tape Measure Verification: 63788

Weather Station: INT00549

Control Panel: 005644

Linear Transducers: 64367, 64278, 64306, 62182, 62354

SECTION 5**LIST OF OFFICIAL OBSERVERS**

NAME	COMPANY
Timothy J. McGill	Intertek B&C
Richard E. Hartman III	Intertek B&C

TEST REPORT FOR SEOHAN ANTAMINE CO. LTD

Report No.: L3571.04-109-44

Revision: 1

Date: 01/15/21

SECTION 6

TEST SPECIMEN DESCRIPTION

Product Type: Wall Cladding

Series/Model: HPL

Product Size(s):

Test Specimens #1 - #6:

OVERALL AREA:	WIDTH		HEIGHT	
	millimeters	inches	millimeters	inches
3.0 m ² (32.0 ft ²)				
Overall size	1219	48	2438	96

Wall Construction: The test specimen was installed onto a test wall constructed from 16-gauge, 2x6 steel studs spaced 16" on center. A 2 mil thick plastic film was loosely draped over the test wall to enable attainment of pressure. The wall was wrapped with #2 Spruce-Pine-Fir nominal 2x8 lumber.

Panel Construction and Installation: The interior and exterior skin was constructed from a 0.006" thick layer of high pressure laminate. The core was constructed from 0.300" thick Kraft paper impregnated with melamine resin. The overall thickness for the panel measured 0.312". Each panel was pre-drilled and installed using #8 x 1-1/4" self-drilling pancake head screws spaced 3/4" from the edges and spaced 16" on center horizontally and vertically.

TEST REPORT FOR SEOHAN ANTAMINE CO. LTD

Report No.: L3571.04-109-44

Revision: 1

Date: 01/15/21

SECTION 7

TEST RESULTS

The temperature during testing was 14 - 20°C (57 - 70°F). All loads were held for 10 seconds. All deflections and permanent sets were taken across the midspan of the panel. Reference Sketch #1 for deflection locations. The results are tabulated as follows:

Test Specimen #1: Negative Loads

TEST PRESSURE Pa (psf)	UNIFORM LOAD DEFLECTION mm (in)	UNIFORM LOAD STRUCTURAL mm (in)	NOTES
-7182 Pa (-150.0 psf)	23.4 mm (0.92")	2.5 mm (0.10")	1
-7661 Pa (-160.0 psf)	25.9 mm (1.02")	3.3 mm (0.13")	1
-8140 Pa (-170.0 psf)	17.3 mm (0.68")	4.1 mm (0.16")	1, 2
-8618 Pa (-180.0 psf)	18.5 mm (0.73")	4.3 mm (0.17")	1
-9097 Pa (-190.0 psf)	19.8 mm (0.78")	4.3 mm (0.17")	1
-9576 Pa (-200.0 psf)	21.1 mm (0.83")	4.6 mm (0.18")	1
-10,055 Pa (-210.0 psf)	N/A	N/A	3

Test Specimen #2: Negative Loads

TEST PRESSURE Pa (psf)	UNIFORM LOAD DEFLECTION mm (in)	UNIFORM LOAD STRUCTURAL mm (in)	NOTES
-8618 Pa (-180.0 psf)	18.0 mm (0.71")	1.8 mm (0.07")	1
-9097 Pa (-190.0 psf)	18.0 mm (0.71")	2.3 mm (0.09")	1
-9576 Pa (-200.0 psf)	19.6 mm (0.77")	2.3 mm (0.09")	1
-10,055 Pa (-210.0 psf)	21.1 mm (0.83")	2.5 mm (0.10")	1
-10,534 Pa (-220.0 psf)	22.9 mm (0.90")	3.0 mm (0.12")	1
-11,012 Pa (-230.0 psf)	24.6 mm (0.97")	3.3 mm (0.13")	1
-11,491 Pa (-240.0 psf)	N/A	N/A	4

TEST REPORT FOR SEOHAN ANTAMINE CO. LTD

Report No.: L3571.04-109-44

Revision: 1

Date: 01/15/21

Test Specimen #3: Negative Loads

TEST PRESSURE Pa (psf)	UNIFORM LOAD DEFLECTION mm (in)	UNIFORM LOAD STRUCTURAL mm (in)	NOTES
-8618 Pa (-180.0 psf)	16.8 mm (0.66")	2.5 mm (0.10")	1
-9097 Pa (-190.0 psf)	18.0 mm (0.71")	2.5 mm (0.10")	1
-9576 Pa (-200.0 psf)	19.1mm (0.75")	2.8 mm (0.11")	1
-10,055 Pa (-210.0 psf)	20.3 mm (0.80")	2.8 mm (0.11")	1
-10,534 Pa (-220.0 psf)	21.8 mm (0.86")	3.3 mm (0.13")	1
-11,012 Pa (-230.0 psf)	23.1 mm (0.91")	3.3 mm (0.13")	1
-11,491 Pa (-240.0 psf)	N/A	N/A	5

Test Specimen #4: Positive Loads

TEST PRESSURE Pa (psf)	UNIFORM LOAD DEFLECTION mm (in)	UNIFORM LOAD STRUCTURAL mm (in)	NOTES
+8618 Pa (+180.0 psf)	13.7 mm (0.54")	1.8 mm (0.07")	1
+9097 Pa (+190.0 psf)	14.7 mm (0.58")	2.0 mm (0.08")	1
+9576 Pa (+200.0 psf)	15.2mm (0.60")	2.3 mm (0.09")	1
+10,055 Pa (+210.0 psf)	16.3 mm (0.64")	2.0 mm (0.08")	1
+10,534 Pa (+220.0 psf)	17.0 mm (0.67")	2.3 mm (0.09")	1
+11,012 Pa (+230.0 psf)	17.8 mm (0.70")	2.5 mm (0.10")	1

Test Specimen #5: Positive Loads

TEST PRESSURE Pa (psf)	UNIFORM LOAD DEFLECTION mm (in)	UNIFORM LOAD STRUCTURAL mm (in)	NOTES
+8618 Pa (+180.0 psf)	14.0 mm (0.55")	1.8 mm (0.07")	1
+9097 Pa (+190.0 psf)	14.5 mm (0.57")	2.0 mm (0.08")	1
+9576 Pa (+200.0 psf)	15.0 mm (0.59")	2.0 mm (0.08")	1
+10,055 Pa (+210.0 psf)	16.0 mm (0.63")	2.3 mm (0.09")	1
+10,534 Pa (+220.0 psf)	16.5 mm (0.65")	2.5 mm (0.10")	1
+11,012 Pa (+230.0 psf)	17.5 mm (0.69")	2.5 mm (0.10")	1

TEST REPORT FOR SEOHAN ANTAMINE CO. LTD

Report No.: L3571.04-109-44

Revision: 1

Date: 01/15/21

Test Specimen #6: Positive Loads

TEST PRESSURE Pa (psf)	UNIFORM LOAD DEFLECTION mm (in)	UNIFORM LOAD STRUCTURAL mm (in)	NOTES
+8618 Pa (+180.0 psf)	14.5 mm (0.57")	2.0 mm (0.08")	1
+9097 Pa (+190.0 psf)	15.2 mm (0.60")	2.5 mm (0.10")	1
+9576 Pa (+200.0 psf)	16.3 mm (0.64")	2.8 mm (0.11")	1
+10,055 Pa (+210.0 psf)	17.3 mm (0.68")	3.0 mm (0.12")	1
+10,534 Pa (+220.0 psf)	17.8 mm (0.70")	3.0 mm (0.12")	1
+11,012 Pa (+230.0 psf)	18.8 mm (0.74")	3.0 mm (0.12")	1

General Note: All testing was performed in accordance with the referenced standard(s).

Note 1: No damage observed.

Note 2: Steel studs were reinforced, testing was continued.

Note 3: Test specimen failed prior to target pressure. Screw heads broke off and a crack developed in the panel.

Note 4: Test specimen failed 1 second into target load. Panel broke at the fastener locations.

Note 5: Test specimen failed 6 seconds into target load. Top of panel broke off.

TEST REPORT FOR SEOHAN ANTAMINE CO. LTD


Report No.: L3571.04-109-44

Revision: 1

Date: 01/15/21

SECTION 8

SKETCH



Sketch #1
Deflection Locations

TEST REPORT FOR SEOHAN ANTAMINE CO. LTD

Report No.: L3571.04-109-44

Revision: 1

Date: 01/15/21

SECTION 9

PHOTOGRAPHS




Photo No. 1
View of Test Specimen #1

TEST REPORT FOR SEOHAN ANTAMINE CO. LTD

Report No.: L3571.04-109-44

Revision: 1

Date: 01/15/21



Photo No. 2
View of Test Specimen #2

TEST REPORT FOR SEOHAN ANTAMINE CO. LTD

Report No.: L3571.04-109-44

Revision: 1

Date: 01/15/21



Photo No. 3
View of Test Specimen #3

TEST REPORT FOR SEOHAN ANTAMINE CO. LTD

Report No.: L3571.04-109-44

Revision: 1

Date: 01/15/21



Photo No. 4
View of Test Specimen #4

TEST REPORT FOR SEOHAN ANTAMINE CO. LTD

Report No.: L3571.04-109-44

Revision: 1

Date: 01/15/21



Photo No. 5
View of Test Specimen #5

TEST REPORT FOR SEOHAN ANTAMINE CO. LTD

Report No.: L3571.04-109-44

Revision: 1

Date: 01/15/21



Photo No. 6
View of Test Specimen #6

TEST REPORT FOR SEOHAN ANTAMINE CO. LTD

Report No.: L3571.04-109-44

Revision: 1

Date: 01/15/21

SECTION 10**DRAWINGS**

The test specimen drawings were not provided by the client.

SECTION 11**REVISION LOG**

REVISION #	DATE	PAGES	REVISION
0	01/14/21	N/A	Original Report Issue
1	01/15/21	5	Added reference to Sketch #1
		8	Inserted Sketch #1